


DIMENSIONS



SC cut quartz crystal
SMT Clock oscillator in ceramic package
Fundamental quartz mode frequency
Ultra Low stability
High shock and vibration resistance
Wide temperature range
Low aging
Ultra low MSL
Very fast start-up
Excellent solderability
Swiss made quality
Customer specification on request

DESCRIPTION:

This SMD oscillator in ceramic package has been specially designed for surface mount using infrared, vapor phase or epoxy techniques.

APPLICATIONS:

- Downhole and Well drilling equipments
- Avionics
- Airbone equipments
- Geothermal equipments
- Fire fighter equipments

The MCSO1's are supplied on trays (91 pcs / tray)
For pick-and-place equipment, the parts are available in 16mm tapes with 250 parts min
1000 parts max

ELECTRICAL CHARACTERISTICS AT +25°C

Frequency stability Over temperature range R = -10 to +150°C (see ordering info) Including 2)*	$\Delta F/F$	$\leq \pm 50$	ppm
Frequency stability Over temperature range S = -10 to +175°C (see ordering info) Including 2)*	$\Delta F/F$	$\leq \pm 100$	ppm
Frequency stability Over temperature range T = -10 to +200°C (see ordering info) Including 2)* 3)*	$\Delta F/F$	$\leq \pm 150$	ppm
Supply voltage $\pm 5\%$ 1)*	Vdd	2.5 / 3.3 / 5	V
Input current	Idd	see table 1	
Output signal		HC-MOS compatible	
Symmetry at Vdd/2		40 / 60	%
Rise & fall time (load 15pf 20% to 80%)		25	ns
Level "0" & "1"		$<0.4 > V_{dd}-0.5$	V
Start-up time	t	<5	ms
Load min / max		3/27	pF

* 1) C = 47nF ceramic must be connected between GND & Vdd
Operable over 2.3 to 5.5V
* 2) adjustment at +25°C, long term aging 1 year
over supply voltage $\pm 5\%$ and over load min to max
* 3) Only available with Supply voltage 5V

TABLE 1: I_{dd}
(With load 10pF)

Frequency	F=32 kHz
W=V _{dd} = 2.5V	< 100µA
V=V _{dd} = 3.3V	< 110µA
blank=V _{dd} = 5V	< 120µA

STANDARD FREQUENCIES:

Frequency «kHz»
32.768
Other frequencies on request

ENVIRONMENTAL CHARACTERISTICS:

Storage temp. range	-65 to +125°C
Vibration resistance	10 to 2000Hz / 40g
Shocks resistance	10000g / 0.3ms / ½ sine

TERMINATIONS AND PROCESSING:

Reflow soldering	+260°C / 10s max
Package	Ceramic 8 x 4 x 2mm
Lids (standard)	Kovar
Lids (on request)	Ceramic Height 2.5mm type MCSO1ELSC
Terminations option T3 on request (not available on G temperature range)	with tinned Ag/Cu/Zn
E/D option 1 on request Reaction time < 5mS	Pin 1 open → Pin 3 Clock H → Clock L → Low

- No power E/D function (pin 1) before V_{dd} is setting on
- Disable option (consumption ≤5µA).

PRODUCT DESCRIPTION AND ORDERING INFORMATION:

MCSO1ELS C V - S 32kHz E/D T3 XXX

C = Ceramic lids
blank = Kovar lids

W = V_{dd} 2.5V
V = V_{dd} 3.3V
blank = V_{dd} 5V

R = -10 to 150°C
S = -10 to 175°C
T = -10 to 200°C
X = custom

Frequency _____

option 1 E/D enable / disable

option 2 blank Au plated
T3 = tinned

customer spec N° _____

A unique part number will be generated for each product specification: i.e:
20xxxx-EA00 xxx pcs (in foam tray)
200xxx-ML00 xxx pcs (in tape & reel, any quantity)

All specifications subject to change without notice.



Micro Crystal AG
Mühlestrasse 14
CH-2540 Grenchen
Switzerland

Tel. +41 32 655 82 82
Fax +41 32 655 82 83
sales@microcrystal.com
www.microcrystal.com