

<HC-49U/S-SMD・HC-49U/S-SMD-L 表面実装タイプ>

2023/5/30 時点(1/2)

*は-Lタイプ

*色付きセルのものはサンプル在庫のあるもの

仕様番号	周波数	発振モード	常温偏差	温度特性	温度範囲	CL	ESR	DL
-	(MHz)	-	(ppm)	(ppm)	(°C)	(pF)	(Ω)	(μW)
TMD-X-2017	3.579545	基本波	±50	±50	-10/+70	16	140	100
TMD-X-2039	3.579545	基本波	±50	±50	-20/+70	16	140	100
TMD-X-2062	3.579545	基本波	±30	±50	-40/+85	12	140	50
TMD-X-2092	3.579545	基本波	±50	±50	-20/+70	12	140	100
TMD-X-2093	3.579545	基本波	±50	±50	-40/+85	16	140	100
TMD-X-2110*	3.579545	基本波	±30	±30	-20/+70	12	140	50
TMD-X-2112	3.579545	基本波	±30	±30	-20/+70	12	140	50
TMD-X-2063	3.686400	基本波	±30	±50	-40/+85	12	140	50
TMD-X-2095	3.686400	基本波	±30	±30	-10/+60	16	140	50
TMD-X-2109*	3.686400	基本波	±30	±50	-40/+85	12	140	50
TMD-X-2008	4.000000	基本波	±50	±50	-10/+70	12	115	100
TMD-X-2018	4.000000	基本波	±50	±50	-10/+70	16	120	100
TMD-X-2064	4.000000	基本波	±30	±50	-40/+85	12	120	50
TMD-X-2024	4.096000	基本波	±30	±50	-10/+70	16	120	100
TMD-X-2032	4.194304	基本波	±15	±20	-20/+70	10	80	100
TMD-X-2033	4.915200	基本波	±50	±50	-10/+70	12	120	100
TMD-X-2057	4.915200	基本波	±50	±50	-10/+70	12	100	10
TMD-X-2065	4.915200	基本波	±30	±50	-40/+85	12	120	50
TMD-X-2098*	4.915200	基本波	±30	±50	-40/+85	12	120	50
TMD-X-2108	4.915200	基本波	±30	±50	-40/+85	16	80	100
TMD-X-2041	5.000000	基本波	±50	±50	-20/+70	16	80	100
TMD-X-2066	5.000000	基本波	±30	±50	-40/+85	12	80	50
TMD-X-2004	6.000000	基本波	±50	±50	-10/+60	16	60	100
TMD-X-2067	6.000000	基本波	±30	±50	-40/+85	12	60	50
TMD-X-2025	6.250000	基本波	±50	±50	-10/+70	16	60	100
TMD-X-2014	7.000000	基本波	±50	±50	-10/+70	12	50	100
TMD-X-2016	7.000000	基本波	±50	±50	-10/+70	16	50	100
TMD-X-2059	7.000000	基本波	±20	±30	-10/+70	16	50	100
TMD-X-2040	7.142400	基本波	±50	±50	-10/+70	16	50	100
TMD-X-2091	7.370000	基本波	±50	±50	-10/+70	16	45	100
TMD-X-2048	7.372800	基本波	±50	±50	-10/+60	16	50	100
TMD-X-2068	7.372800	基本波	±30	±50	-40/+85	12	50	50
TMD-X-2020	7.680000	基本波	±30	±30	-40/+85	16	50	100
TMD-X-2089	7.987200	基本波	±30	±50	-40/+85	12	50	100
TMD-X-2100	7.987200	基本波	±50	±50	-30/+65	16	50	100
TMD-X-2102	7.987200	基本波	±50	±50	-30/+65	12	50	100
TMD-X-2013	8.000000	基本波	±30	±50	-30/+85	16	50	100
TMD-X-2042	8.000000	基本波	±50	±50	-10/+70	16	50	100
TMD-X-2069	8.000000	基本波	±30	±50	-40/+85	12	50	50
TMD-X-2105	8.000000	基本波	±30	±30	-20/+70	16	50	100
TMD-X-2051	8.192000	基本波	±30	±50	-10/+60	16	50	100
TMD-X-2099*	8.388608	基本波	±30	±30	-10/+70	16	50	50
TMD-X-2047	9.216000	基本波	±50	±50	-20/+70	16	45	100
TMD-X-2044	9.509390	基本波	±50	±50	-20/+70	16	45	100
TMD-X-2034	9.830400	基本波	±30	±50	-10/+60	18	100	100
TMD-X-2070	9.830400	基本波	±30	±50	-40/+85	12	45	50
TMD-X-2096*	9.830400	基本波	±30	±50	-40/+85	12	45	50
TMD-X-2101	9.830400	基本波	±50	±50	-30/+65	8	50	100
TMD-X-2103	9.830400	基本波	±50	±50	-10/+70	18	45	100
TMD-X-2001	10.000000	基本波	±50	±50	-10/+60	16	45	100
TMD-X-2006	10.000000	基本波	±30	±30	-40/+85	16	45	100
TMD-X-2006B	10.000000	基本波	±30	±30	-30/+85	16	45	100
TMD-X-2021	10.000000	基本波	±30	±30	-40/+85	16	45	100
TMD-X-2049	10.000000	基本波	±50	±50	-40/+85	16	45	100
TMD-X-2052	10.000000	基本波	±30	±20	-10/+60	16	45	100
TMD-X-2071	10.000000	基本波	±30	±50	-40/+85	12	45	100
TMD-X-2104	10.000000	基本波	±30	±50	-20/+70	18	45	100
TMD-X-2106	10.000000	基本波	±30	±30	-20/+70	16	45	100
TMD-X-2007	11.059200	基本波	±50	±50	-10/+70	12	40	100
TMD-X-2038	11.059200	基本波	±30	±100	-55/+125	20	50	100

<HC-49U/S-SMD・HC-49U/S-SMD-L 表面実装タイプ>

2023/5/30 時点(2/2)

*は-Lタイプ

*色付きセルのものはサンプル在庫のあるもの

仕様番号	周波数	発振モード	常温偏差	温度特性	温度範囲	CL	ESR	DL
-	(MHz)	-	(ppm)	(ppm)	(°C)	(pF)	(Ω)	(μW)
TMD-X-2072	11.059200	基本波	±30	±50	-40/+85	12	45	50
TMD-X-2005	12.000000	基本波	±50	±50	-10/+60	16	30	100
TMD-X-2036	12.000000	基本波	±50	±50	-10/+70	16	45	100
TMD-X-2037	12.000000	基本波	±30	±50	-40/+85	16	45	100
TMD-X-2073	12.000000	基本波	±30	±50	-40/+85	12	45	50
TMD-X-2107	12.000000	基本波	±30	±30	-20/+70	16	45	100
TMD-X-2011	12.288000	基本波	±50	±50	-10/+60	12	45	100
TMD-X-2019	12.288000	基本波	±50	±50	-10/+70	16	45	100
TMD-X-2083	12.288000	基本波	±30	±50	-40/+85	12	45	50
TMD-X-2009	12.500000	基本波	±50	±50	-20/+70	16	45	100
TMD-X-2058	12.500000	基本波	±50	±50	-10/+70	12	45	100
TMD-X-2090	12.500000	基本波	±50	±100	-40/+125	12	50	100
TMD-X-2113	12.500000	基本波	±30	±50	-40/+85	12	45	50
TMD-X-2097	12.800000	基本波	±50	±50	-40/+85	10	45	10
TMD-X-2084	13.500000	基本波	±30	±50	-40/+85	12	35	50
TMD-X-2074	14.318180	基本波	±30	±50	-40/+85	12	35	50
TMD-X-2075	14.745600	基本波	±30	±50	-40/+85	12	35	50
TMD-X-2085	15.000000	基本波	±30	±50	-40/+85	12	35	50
TMD-X-2002	16.000000	基本波	±50	±50	-10/+60	16	35	100
TMD-X-2010	16.000000	基本波	±50	±50	-10/+70	12	35	100
TMD-X-2045	16.000000	基本波	±50	±50	-10/+70	16	35	100
TMD-X-2046	16.000000	基本波	±50	±50	-10/+60	16	35	100
TMD-X-2076	16.000000	基本波	±30	±50	-40/+85	12	35	50
TMD-X-2055	16.384000	基本波	±50	±50	-10/+70	16	35	100
TMD-X-2077	16.384000	基本波	±30	±50	-40/+85	12	35	50
TMD-X-2086	16.934400	基本波	±30	±50	-40/+85	12	35	50
TMD-X-2114	18.432000	基本波	±30	±50	-40/+85	12	35	50
TMD-X-2060	19.660800	基本波	±50	±50	-10/+70	12	30	100
TMD-X-2078	19.660800	基本波	±30	±50	-40/+85	12	35	50
TMD-X-2022	20.000000	基本波	±30	±30	-40/+85	16	30	100
TMD-X-2027	20.000000	基本波	±30	±50	-40/+85	18	30	100
TMD-X-2031	20.000000	基本波	±50	±50	-10/+70	12	30	100
TMD-X-2053	20.000000	基本波	±30	±20	-10/+60	16	30	100
TMD-X-2079	20.000000	基本波	±30	±50	-40/+85	12	30	50
TMD-X-2023	24.000000	基本波	±30	±30	-40/+85	16	30	100
TMD-X-2030	24.000000	基本波	±50	±50	-10/+70	12	30	100
TMD-X-2080	24.000000	基本波	±30	±50	-40/+85	12	30	50
TMD-X-2015	24.576000	基本波	±50	±50	-10/+70	12	30	100
TMD-X-2081	24.576000	基本波	±30	±50	-40/+85	12	30	50
TMD-X-2094*	24.576000	基本波	±50	±50	-20/+70	12	30	100
TMD-X-2028	25.000000	基本波	±30	±50	-40/+85	18	30	100
TMD-X-2029	25.000000	基本波	±30	±30	-40/+85	16	30	100
TMD-X-2043	25.000000	基本波	±50	±50	-10/+60	16	30	100
TMD-X-2056	25.000000	基本波	±50	±50	-10/+70	12	10	100
TMD-X-2082	25.000000	基本波	±30	±50	-40/+85	12	30	50
TMD-X-2115	25.000000	基本波	±20	±50	-40/+85	10	30	50
TMD-X-2012	27.000000	基本波	±50	±50	-40/+85	16	30	100
TMD-X-2035	27.000000	基本波	±20	±30	-10/+70	16	30	100
TMD-X-2087	27.000000	基本波	±30	±50	-40/+85	12	30	50
TMD-X-2088	28.636360	基本波	±30	±50	-40/+85	12	30	50
TMD-X-2026	30.000000	基本波	±50	±50	-40/+85	12	30	100
TMD-X-2050	31.808000	基本波	±30	±50	-10/+60	8	30	100