

<HC-49U/S リードタイプ>

*色付きセルのものはサンプル在庫のあるもの

2023/5/30 時点(1/2)

仕様番号	周波数 (MHz)	発振モード	常温偏差 (ppm)	温度特性 (ppm)	温度範囲 (°C)	CL (pF)	ESR (Ω)	DL (μW)
TMD-X-1025	3.579545	基本波	±50	±50	-10/+70	16	140	100
TMD-X-1010	4.000000	基本波	±50	±50	-10/+70	12	115	100
TMD-X-1042	4.000000	基本波	±50	±50	-40/+85	12	120	100
TMD-X-1057	4.000000	基本波	±30	±30	-20/+70	12	120	100
TMD-X-1065	4.000000	基本波	±20	±30	-10/+70	16	120	50
TMD-X-1045	4.194304	基本波	±18	±10	+5/+35	9	100	50
TMD-X-1011	4.915200	基本波	±50	±50	-10/+70	12	115	100
TMD-X-1039	4.915200	基本波	±50	±50	-20/+70	16	120	50
TMD-X-1043	4.915200	基本波	±50	±50	-40/+85	12	100	100
TMD-X-1051	4.915200	基本波	±50	±50	-20/+70	16	120	50
TMD-X-1047	5.000000	基本波	±50	±100	-40/+125	20	80	100
TMD-X-1058	5.000000	基本波	±30	±30	-20/+70	16	80	100
TMD-X-1063	5.000000	基本波	±20	±30	-10/+70	16	80	50
TMD-X-1002	6.000000	基本波	±50	±50	-10/+60	16	60	100
TMD-X-1037	6.000000	基本波	±50	±50	-20/+70	12	80	100
TMD-X-1012	7.000000	基本波	±50	±50	-10/+70	12	45	100
TMD-X-1066	7.159000	基本波	±20	±30	-10/+70	16	50	50
TMD-X-1026	7.372800	基本波	±50	±50	-10/+70	16	50	100
TMD-X-1040	7.372800	基本波	±50	±50	-10/+70	16	50	100
TMD-X-1055	7.500000	基本波	±30	±50	-10/+70	16	50	100
TMD-X-1013	7.600000	基本波	±50	±50	-10/+70	12	45	100
TMD-X-1067	7.680000	基本波	±20	±30	-10/+70	16	50	50
TMD-X-1009	8.000000	基本波	±50	±50	-10/+70	16	45	100
TMD-X-1023	8.000000	基本波	±50	±50	-10/+70	12	50	100
TMD-X-1049	8.000000	基本波	±50	±50	-40/+85	16	50	100
TMD-X-1059	8.000000	基本波	±30	±30	-20/+70	16	50	100
TMD-X-1068	8.000000	基本波	±20	±30	-10/+70	16	50	50
TMD-X-1031	9.830400	基本波	±50	±50	-10/+60	16	45	100
TMD-X-1046	9.830400	基本波	±50	±50	-40/+85	12	45	10
TMD-X-1056	9.830400	基本波	±30	±50	-10/+70	16	45	100
TMD-X-1021	10.000000	基本波	±50	±50	-10/+60	16	45	100
TMD-X-1029	10.000000	基本波	±50	±50	-20/+70	12	45	100
TMD-X-1033	10.000000	基本波	±50	±50	-10/+70	16	30	100
TMD-X-1044	10.000000	基本波	±50	±50	-40/+85	12	60	100
TMD-X-1054	10.000000	基本波	±30	±50	-10/+70	16	45	100
TMD-X-1060	10.000000	基本波	±30	±30	-20/+70	16	45	100
TMD-X-1069	10.000000	基本波	±20	±30	-10/+70	16	45	50
TMD-X-1014	11.059200	基本波	±50	±50	-10/+70	12	40	100
TMD-X-1003	12.000000	基本波	±50	±50	-10/+60	16	35	100
TMD-X-1019	12.000000	基本波	±50	±50	-10/+70	12	45	100
TMD-X-1070	12.000000	基本波	±20	±30	-10/+70	16	45	50
TMD-X-1004	12.288000	基本波	±50	±50	-10/+60	16	35	100
TMD-X-1030	12.288000	基本波	±50	±50	-20/+70	16	45	100
TMD-X-1038	12.288000	基本波	±50	±50	-40/+85	16	45	100
TMD-X-1015	12.500000	基本波	±50	±50	-10/+60	16	35	100
TMD-X-1048	12.500000	基本波	±50	±50	-40/+85	12	45	100
TMD-X-1027	14.745600	基本波	±50	±50	-10/+70	16	35	100
TMD-X-1032	14.745600	基本波	±50	±50	-40/+85	18	35	100
TMD-X-1006	16.000000	基本波	±50	±50	-10/+60	16	30	100
TMD-X-1024	16.000000	基本波	±30	±100	-40/+85	16	30	100
TMD-X-1050	16.000000	基本波	±50	±50	-20/+70	12	30	100
TMD-X-1061	16.000000	基本波	±30	±30	-20/+70	16	35	100
TMD-X-1071	16.000000	基本波	±20	±30	-10/+70	16	35	50
TMD-X-1028	16.384000	基本波	±50	±50	-10/+70	16	35	100
TMD-X-1036	16.384000	基本波	±50	±50	-20/+70	16	35	100
TMD-X-1074	18.432000	基本波	±30	±30	-10/+70	16	35	50
TMD-X-1008	19.660800	基本波	±50	±50	-10/+70	16	30	100
TMD-X-1016	20.000000	基本波	±50	±50	-10/+60	16	30	100
TMD-X-1034	20.000000	基本波	±50	±50	-10/+70	16	20	100
TMD-X-1041	20.000000	基本波	±50	±50	-40/+85	12	30	100
TMD-X-1072	20.000000	基本波	±20	±30	-10/+70	16	30	50
TMD-X-1073	24.000000	基本波	±20	±30	-10/+70	16	30	50

<HC-49U/S リードタイプ>

*色付きセルのものはサンプル在庫のあるもの

2022/12/18 時点(2/2)

仕様番号	周波数 (MHz)	発振モード	常温偏差 (ppm)	温度特性 (ppm)	温度範囲 (°C)	CL (pF)	ESR (Ω)	DL (μW)
-	-	-	-	-	-	-	-	-
TMD-X-1017	24.576000	基本波	±50	±50	-10/+70	12	30	100
TMD-X-1022	25.000000	基本波	±50	±50	-10/+60	16	30	100
TMD-X-1052	25.000000	基本波	±30	±50	-10/+70	12	30	50
TMD-X-1053	25.000000	基本波	±30	±50	-10/+70	16	30	50
TMD-X-1064	25.000000	基本波	±20	±30	-10/+70	16	30	50
TMD-X-1035	30.000000	基本波	±50	±50	-10/+70	16	30	100
TMD-X-1020	32.000000	基本波	±50	±50	-10/+60	16	30	100
TMD-X-1062	32.000000	基本波	±30	±30	-20/+70	16	30	100